SV35X

MINI SKID STEER LOADER

COMPACT SIZE. SERIOUS CAPABILITY.

38 HP	70 L/MIN	700 KG	1,060 MM
KUBOTA V1505	AUXILIARY FLOW	RATED CAPACITY	MACHINE WIDTH
4-CYLINDER DIESEL	HIGH-FLOW HYDRAULICS	OPERATING CAPACITY	WITHOUT BUCKET

Premium hydraulic components. Smooth pilot controls. Built for demanding attachments.

TECHNICAL SPECIFICATIONS

Boleo SV35X

GENERAL	
Width without standard bucket	**1,060 mm**
Length without standard bucket	**2,272 mm**
Overall height	**1,470 mm**
Maximum operating height	**3,030 mm**
Maximum hinge-pin height	**2,220 mm**
Ground clearance	**220 mm**
Operating weight	**1,600 kg**
Rated operating capacity	**700 kg**
Tipping capacity	**1,629 kg**

POWER	
Engine	**Kubota V1505 - Made in Japan**
Fuel type	**Diesel**
Cooling system	**Liquid cooled**
Cylinders	**4-cylinder, 4-stroke**
Displacement	**1.498 L**
Gross engine power	**38 HP @ 3,000 rpm**

FLUID CAPACITIES	
Fuel tank	**40 L**
Engine oil with filter	**4.0 L**
Hydraulic reservoir	**32 L**

HYDRAULIC SYSTEM	
Hydraulic pump make	**HANSA/FLEX - Made in Italy**
Pump type	**Variable displacement**
Auxiliary hydraulic flow	**70 L/min**
Auxiliary relief pressure	**180 bar**
Hydraulic flow control	**3-mode: Low / Medium / High**
Control valves	**Bosch Rexroth**

DRIVE & TRACKS	
Drive system	**Hydrostatic transmission**
Drive motor make	**POCLAIN - Made in Germany**
Motor type	**Radial piston**
Track configuration	**Sprocket drive, 8 rollers per side**
Track width	**230 mm**
Travel speed	**8.0 km/h**

OPERATOR & ATTACHMENT INTERFACE	
Operator controls	**Two hydraulic pilot-operated joysticks**
Quick coupler	**Stucchi Quick Release**
Quick mount plate	**Mini universal / Bobcat-style plate**
Electrical system	**12 V**

Specifications are subject to change without notice. Equipment shown may include optional attachments or components.